

## Safety Harness

Universal harnesses are lightweight, inexpensive, and simple to use. Size versatility makes the unit cost effective for multiple users. Each Guardian harness incorporates our Impact Indicator to make inspection easier. Meets all applicable OSHA and ANSI standards.

### Standard Features:

- Impact Indicator shows if the product has been in a fall
- Comfortable Nylon Webbing
- Notched Pass-Thru Chest Buckles
- Sub-Pelvic Strap distributes the weight of a fall
- No-Loose-Ends Shoulder Strap design



Universal Safety Harness		
01100	SM-LG	Pass-Thru Leg Straps
01105	XL	Pass-Thru Leg Straps
01110	SM-LG	Pass-Thru Leg Straps with Side Positioning Rings
01150	SM-LG	Tongue Buckle Leg Straps
01160	SM-LG	Tongue Buckle Leg Straps with Side Positioning Rings

## Lanyard

These **lanyards** are specially designed to withstand additional free fall distance while maintaining maximum allowable impact forces for up to a 10-ft free fall, per OSHA requirements. The HD lanyard can be used as part of a 400 lb max. worker capacity *per fall arresting system* for free falls of 5' or less.

Item ID	Description	Sales Description
01200	SS60-HD	5 ft Single Leg Shock Absorbing HD Lanyard
01202	SS60-HDR	5 ft Single Leg Shock Absorbing HD Lanyard w/Rebar Hook
01210	SS60-2HD	5 ft Double Leg Shock Absorbing Lanyard
01211	SS60-2RHD	5 ft Double Leg Shock Absorbing Lanyard w/Rebar Hook

\*Rebar hooks cannot be used with Beamer Anchors



## Retractable Lifeline

The **Guardian HD Retractable Lifeline** is designed to be used specifically for leading edge work. With an integrated shock pack attached to the cable lifeline, the retractable will keep the arresting forces below 900 lb while at the same time reducing the amount of impact forces on the cable lifeline itself. The ideal position of a retractable, when used as a part of a PFAS, is directly overhead.

Often, contractors will place a retractable on the deck and use it at foot level. Almost all retractables on the market are not allowed to be used in this manner if the worker is exposed to a leading edge hazard.



### Retractable Lifelines

Part #	Size	Description	Weight
10900	11'	1" Nylon Webbing w/ Carabiner, Swivel Top & Snap Hook	9 lb
10901	11'	1" Nylon Webbing w/ Carabiner, Swivel Top & Rebar Hook	11 lb
10909	20'	1" Nylon Webbing w// Swivel Top, Swivel Snap Hook, Carabiner & Tag Line	16 lb
10910	20'	3/16" Galvanized Cable w/ Swivel Top, Swivel Snap Hook, Carabiner & Tag Line	18 lb
10915	30'	3/16" Galvanized Cable w/ Swivel Top, Swivel Snap Hook, Carabiner & Tag Line	21 lb

