



Rigging Shackles



G-209 & S-209 Screw Pin Anchor Shackle Specifications

Nominal Size (in)	Working Load Limit (tons) *	Stock No.		Weight Each (lb)
		G-209 Galv.	S-209 S.C.	
3/16	1/3	1018357011	--	.06
1/4	1/2	1018375011	1018384011	.10
5/16	3/4	1018393011	1018400011	.19
3/8	1	1018419011	1018428011	.31
7/16	1-1/2	1018437011	1018446011	.38
1/2	2	1018455011	1018464011	.72
5/8	3-1/4	1018473011	1018482011	1.37
3/4	4-3/4	1018491011	1018507011	2.35
7/8	6/12	1018516011	1018525011	3.62
1	8-12	1018534011	1018543011	5.03



G-2130 & S-2130 Bolt Type Anchor Shackle

Nominal Shackle Size (in)	Working Load Limit* (tons)	Stock No.		2130 Weight Each (lb)
		G-2130 Galv	S2130 S.C.	
3/16	1/3^	1019464	--	.06
1/4	1/2	1019466011	--	.11
5/16	3/4	1019468011	--	.22
3/8	1	1019470011	--	.33
7/16	1-1/2	1019471011	--	.49
1/2	2	1019472011	1019481011	.79
5/8	3-1/4	1019490011	1019506011	1.68
3/4	4-3/4	1019515011	1019524011	2.72
7/8	6-1/2	1019533011	1019542011	3.95
1	8-1/2	1019551011	1019560011	5.66



G-450 Crosby® Clip Specifications

Rope Size (in)	G-450 Stock No. Galv.	Std. Package Qty.	Weight Per 100 (lb)	Minimum No. of Clips	Rope Turnback (in)	Torque (ft lb)
*1/8	1010015011	100	6	2	3-1/4	4.5
*3/16	1010033011	100	10	2	3-3/4	7.5
1/4	1010051011	100	19	2	4-3/4	15
5/16	1010079011	100	28	2	5-1/4	30
3/8	1010097011	100	48	2	6-1/2	45
7/16	1010113011	50	78	2	7	65
1/2	1010131011	50	80	3	11-1/2	65
9/16	1010159011	50	109	3	12	95
5/8	1010177011	50	110	3	12	95
3/4	1010195011	25	142	4	18	130



G429 Fist Grip® Wire Rope Clip Specifications

Rope Size (in)*	G-429 Stock No. Galv.	Std. Package Qty.	Weight Per 100 (lb)	Minimum No. of Clips	Rope Turnback (in)	Torque (ft lb)
3/16-1/4	1010471011	100	23	2	4	30
5/16	1010499011	100	28	2	5	30
3/8	1010514011	50	40	2	5-1/4	45
7/16-1/2	1010532011	50	62	3	11	65
9/16-5/8	1010550011	50	103	3	13-1/2	130
3/4	1010578011	25	175	3	16	225



Crosby® Swivels

EQUIPPED WITH TAPERED ROLLER THRUST BEARING



- Suitable for frequent rotation under load
- All swivels individually proof tested with certification
- All hooks furnished with latches assembled
- All jaws complete with bolts, nuts, and cotter pins
- Pressure lube fitting provided
- NOT TO BE USED ON DEMOLITION (WRECKING) BALLS
- Other types and capacities up to 1,250 tons available to meet your requirements
- **IMPORTANT - Crosby Swivel should only be used with the recommended wire rope. Contact the wire rope manufacturer for the proper wire rope to be used with Crosby Swivels.**



Crosby® Swivels



Swivel Number (Type)	Stock No. S.C.	Working Load Limit* (metric tons)	Wire Rope Size (in)	Weight Each (lb)
3-S-1	297011	3	1/2	9.81
3-S-2	297020	3	1/2	9.63
3-S-3	297039	3	1/2	9.12
3-S-4	2970480	3	1/2	9.00
3-S-5	2970570	3	1/2	8.50
3-S-6	297066	3	1/2	9.32
5-S-1	297217	5	5/8	15.51
5-S-2	297226	5	5/8	13.69
5-S-3	297235	5	5/8	13.50
5-S-4	297244	5	5/8	12.33
5-S-5	2972530	5	5/8	11.30
5-S-6	297262	5	5/8	14.24
8-1/2-S-1	2974130	8-1/2	3/4	29.42
8-1/2-S-2	297422	8-1/2	3/4	26.16
8-1/2-S-3	297431	8-1/2	3/4	24.90
8-1/2-S-4	297440	8-1/2	3/4	29.00
8-1/2-S-5	2974590	8-1/2	3/4	29.25
8-1/2-S-6	297468	8-1/2	3/4	32.00
10-S-1	2976180	10	7/8	46.75
10-S-2	297627	10	7/8	45.75
10-S-3	297636	10	7/8	43.50
10-S-4	297645	10	7/8	44.00
10-S-5	297654	10	7/8	42.00
10-S-6	297663	10	7/8	45.50



Individually proof tested to 2x the Working Load Limit. Ultimate load is 5x the Working Load Limit.

