

SUPERTECHLONTM Round Sling

SUPERTECHLON[™] Round Slings offer a unique blend of strength and flexibility. They are light weight and have superior abrasion resistance.

Features Include:

- Patented abrasion resistant Techlon[™] outer cover delivers up to twice the durability of a standard cover
- Stripe coded to assist in identifying slings capacity (each stripe equals 3,000 lb of vertical capacity)
- Print coded with vertical capacity on outer cover.
- · Color coded for easy identification
- Protected tag feature helps protect tag from illegibility
- Individually serialized for traceability
- Highest capacities per color in the industry



Part No.	Color Code	Rated Capacity *			Min. Length	
i ui t i to	Color Couc	Vertical	Choker	Basket	ivini Dengu	
ST-ENR-3000	Purple	3,000 lb	2,400 lb	6,000 lb	3 ft	
ST-ENR-6000	Green	6,000 lb	4,800 lb	12,000 lb	3 ft	
ST-ENR-9000	Yellow	9,000 lb	7,200 lb	18,000 lb	3 ft	
ST-ENR-12000	Tan	12,000 lb	9,600 lb	24,000 lb	3 ft	
ST-ENR-15000	Red	15,000 lb	12,000 lb	30,000 lb	3 ft.	
ST-ENR-18000	White	18,000 lb	14,400 lb	36,000 lb	6 ft	
ST-ENR-24000	Blue	24,000 lb	19,200 lb	48,000 lb	6 ft	
ST-ENR-30000	Orange	30,000 lb	24,000 lb	60,000 lb	6 ft	
NOTE: Larger capacities are available upon request.						



WARNING: Sling failure can cause DEATH or INJURY resulting from misuse, damage, and excessive wear. Adhere to industry standards and regulations.

Manila Rope

A good all-purpose rope, **Manila Rope** is used extensively in marine, agricultural, trucking, construction, and oil exploration.

Features:

- Inexpensive
- Strongest of the vegetable fibers actually stronger when wet
- Low stretch ideal for applications not requiring high strength or great elasticity
- Absorbs water swells up to 100% of its weight, making handling more difficult
- Storage if wet, dry thoroughly to prevent mildew, rot, or loss of strength
- Very poor chemical resistance



PIN #	Nominal Diameter in	Approx. Wt/ *lb / 100 Ft	Minimum Tensile lb				
08MANR0000	1/4	1.82	540				
10MANR0601	5/16	2.64	900				
12MANR0602	3/8	3.79	1215				
16MANR0602	1/2	6.96	2380				
20MANR0602	5/8	12.7	3960				
24MANR0602	3/4	15.9	4860				
 * Weight will vary slightly. ** Stocked in 600Ft. Cartons (some smaller sizes also in 1200 ft Cartons) *** Available in other diameters upon request 							